

DOSTAB

DOSTAB



WILL DO THE JOB

MANUFACTURED TO THE LATEST API SPEC 7-1 EDITION AND WITH BEST QUALITY, THE DOSTAB WILL DO THE JOB. WHETHER IT IS INTENDED FOR STEERING, VIBRATION DAMPING, OR GAUGE HOLDING, THE DOSTAB IS MADE FROM INDUSTRY STANDARD STEEL GRADES AND SHIELDED WITH SUPERIOR-QUALITY GAUGE PROTECTION TO ACCOMPLISH THE MISSION.

THE DOSTAB CAN BE DESIGNED AND MANUFACTURED WITH HIGH FLEXIBILITY TO SUIT CUSTOMER REQUIREMENTS. NUMBER OF BLADES, BLADE COVERAGE, AND BLADE TAPER ANGLE CAN BE TAILORED TO SATISFY THE APPLICATION. ANY HARDFACING GRADE, WHETHER IT IS THE BASIC HF1000, THE MORE COMPLEX HF4000 WITH TCI BUTTONS, OR THE SUPERIOR QUALITY HF5000,

CAN BE SUPPLIED.

STEEL QUALITY IS STRICTLY CONTROLLED BY ENGINEERING TO MAKE SURE THAT API SPEC 7-1 REQUIREMENTS ARE RESPECTED AND ENSURE

PRIVATE & CONFIDENTIAL

FEATURES:

- HIGH FLEXIBILITY IN DESIGN WITHIN API SPEC 7-1 BOUNDARIES TO SUIT CUSTOMER SPECIFIC APPLICATION.
- LARGE VARIETY OF HARDFACING/ GAUGE PROTECTION OPTIONS.

BENEFITS:

- OPTIMUM DURABILITY TO ENSURE APPLICATION PURPOSE IS SATISFIED, WHETHER IT IS STEERING, VIBRATION DAMPING, OR GAUGE HOLDING.
- ROBUSTNESS, INTEGRITY AND BEST PERFORMANCE OF THE STABILIZER.

DOYEN STANDARD SIZES

HOLE SIZE		5¼" - 6⅞"	7" - 9⅞"	10" - 13"	13½" - 17⅞"	18" - 22"	23" - 28"
DRILL COLLAR RANGE		4⅛" - 5½"	5¾" - 7¼"	7" - 9½"	8" - 10"	8½" - 11"	8½" - 11"
NOMINAL STABILIZER BODY OD		4¾"	6½"	8"	9½"	9½"	9½"
STD STABILIZER OVERALL LENGTH	NEARBIT	68"	72"	75"	85"	95"	101"
	STRING	72"	76"	80"	90"	100"	106"
STD STAB FISHING NECK LENGTH		28"	28"	28"	28"	28"	28"
CROWN LENGTH (MIN)		14"	18"	18"	20"	22"	22"
BLADE WIDTH		2"	2½"	3"	3½"	4"	4"
STD STABILIZER TONG	NEARBIT	22"	20"	20"	23"	23"	23"
SPACE	STRING	22"	20"	20"	23"	23"	23"